



Bus Model:	KLQ6123K&KLQ6113K
Overall dimension	
Seats number:	53+1+1&63+1+1
Fuel tank:(L)	400L
STANDARD CHASSIS	
Engine:	Cummins L360
Clutch:	Sachs Diaphragm spring clutch (Φ430)
Gearbox:	QJ S6-160 with ZF technology gearbox
Retarder	Telma retarder
Propeller shaft:	Strengthen propeller shaft
Suspension:	Spring suspension
Axle:	Fron disc / rear drum axle
Braking:	Dual circuit service braking system Energy storage spring parking brake
Steering:	ZF Power steering
Tyre:	295/80R22.5 tubeless tire
Others:	Automatic fire extinguisher in the engine cabin
STANDARD BODY	
A/C:	Higer roof mounted dependent A/C (BOCK compressor 32000KCal) with ventilation, air filtrating function (improved special for export market)
Seats:	Passenger seats Guide seat with backrest and foot rest Air suspension driver seat
Door:	Front pneumatic out-swing door with remote control key Middle passenger door with remote control key
Window:	Front window with defroster; dark color (side sliding window); 2 emergency exit roof windows
Audiovisual:	Hard disc player with USB+Front 19' fixed LCD, middle 19' LCD
Lighting:	Double line ceiling lamp High position breaking lamp Step lamp Reading lamp
Rear-view:	Electrical rear-view mirror with defroster
Floor:	Anti-attrition floor leatheriod
	Front window one manual sun visor; Thick Cloth curtain for side window(dark color)
	New style Luxury molding ceiling
	New style Luxury dashboard
	Digital clock with thermometer and hygrometer function
	Microphone for co-driver
	2 Emergency exit roof window with ventilation fan
	Bigger Radiator
	Reverse monitor
	Optimized noise isolation
	Optimized air filter
	New style fashionable appearance
	Export configuration

